Screw Down Base Plate Installation Instructions



Whats Included

Cover Plate (Shown face up with masking) Masking to remain on during installation Material: 304 Stainless steel

Allen Wrench For tightening bottom bolt Size: 5 mm Wrench



Floor Plate (Shown face up with included anti-rotation pin) Material: 304 Stainless steel

Bottom Bolt Flat head, 8 MM thread Material: 18-8 Stainless steel

Additional Items



Rubber Band To aid in installation of floor plate and keep cover plate safe



#8 Stainless Screws To secure plate to ground. Exact screw used will vary with flooring. (i.e. wood, cement, etc) [Pilot hole in flooring recommended]



Cordless Drill To install screws and drill pilot holes as needed



Shayne Malone Smalone@artdisplay.com 908.731.7804 www.Q-Cord.com Step 1: Slide cover plate masking up (toward cords) onto the post from the bottom.



Step 3: Align base plate with post. Pin in side hole will prevent rotation.



Step 5: Place base onto floor and orient cords in desired direction. Place posts approx 7' apart



Step 7: Remove rubber band.



Step 2: Use rubber band under cover plate to hold it in position



Step 4: Insert and tighten bottom bolt to create a solid connection.



Step 6: Screw plate to floor using appropriate screws. (Size #8)



Step 8: Remove masking peel coat.

