

H-Track

Product Details:

The H-Track is ideal for environments where the works of art are changed frequently or where it is inappropriate to damage the primary wall surface.

The system is a discreet aluminum extrusion designed to be applied to existing wall surfaces at a high level so that it blends with the ceiling junction and provides a stable point from which to hang artworks using a variety of materials including stainless cables or stainless rods. The system is made in the US and has the option of a white vinyl cover to go on the track.



- **Stainless Steel Rods** provides the most rigid and vertical installation and can support artworks up to 200 lbs. (50 kg) per pair. Comes in a standard stainless steel but can be powder coated a custom color.
- **Stainless Steel Cable** will provide the strongest flexible cable system and can support artworks up to 100 lbs. (35 kg) per pair.

***The GL series of hooks and hangers will only work with the stainless steel cable.**

***Each cable or rod requires a top block.**

***Screws not included due to different use scenarios**

Useful Tips and Guidelines:

We recommend that the track runs continuously along the wall including above any doors or window openings. Even though this part of the track may never be used it maintains a clean visual line that blends with the building, whereas individual sections of track will look fragmented and draw your attention.

The track is not predrilled for hanging so that you can make sure you position your wall anchors into the studs. We usually recommend a screw every 12 -16 inches or so while making sure you are hitting studs. If you wish to hang seriously heavy artworks (more than 300 lbs.) then we recommend drilling more frequent fixing points at every 6" or even 4". The track can then sustain loads of up to 1100 lbs. when supported on the stainless-steel rods. We recommend that you contact us for larger top blocks which will help distribute the load if you are planning to hang seriously heavy artworks.

Installation Instructions:

Hold the first section of track in place and mark the screw holes. Drill and fix the track making sure that it is installed with the 'mouth' of the track pointing down and the screw holes running along the top. Then repeat this process for the second section, making sure that the tracks are aligned properly. Repeat this process until you reach the last section and trim to length. Each track has a small section at the bottom that has a wider slot for allowing the addition or removal of top blocks. When you trim a length of track, make sure you don't cut off this end as you will need that section with the wider slot on the wall.

Hanging Your Artworks:

With stainless cable, feed the cord through the top block and insert from the end or through one of the wider slots on the bottom of the track. With stainless rods, insert two top blocks from the end or through one of the wider slots on the bottom, then screw the rods into place from underneath. Slide the appropriate hook attachment up the cord or rod from the bottom and tighten at the required height with the bolt heads facing toward you. It's much easier to do this with the two lengths side by side so that the hook heights match. For artworks with cord on the back, just place the cord over the hook.

For more information and pricing on the H-Track Hanging System:

Art Display

ESSENTIALS

www.ArtDisplay.com